

SLOPING SCREEN ROL®

“The sloping screen ROL®, our classic, has a very good ability to screen any kind of product from 1 to 300 mm, wet or dry. ,”



1 | CUSTOMIZED DESIGN


All design criteria such as speed, cuts, particle size distribution, humidity, temperature, etc. are integrated to fit the basic parameters of our machines like the surface, the amplitude and the frequency of vibration, the slope and the correct equipment (water spraying device, special cloths, cleaning systems, etc.).


2 | APPLICATIONS

- Public works and mining industry
- Chemical
- Food
- Environment
- Metallurgy


3 | USES

- SIZING material dry or wet
- SEPARATION (of good product and particles to be eliminated)
- WASHING
- CLASSIFYING







8 REQUIRED SPACE
Fully adjustable to your space constraints within the limits of design rules



7 FINISH
• Galvanized
• Painted
• Stainless steel




6 COUPLING
• Pulleys and belts
• Universal joint




5 ERGONOMICS
Large space between the decks till 850 mm



4 WATER SPRAYING
• Static or vibrating
• In option



3 SUPPORT FRAME
Fully adjustable




2 SECURING EQUIPMENT
• Either lateral or longitudinal tightening
• By clamping
• Either by fitting (modular panels)




1 SUSPENSION
By helical springs



9 STATIC HOOD & VIBRATING BODY
• Bored, assembled and bolted
• Fully removable




10 EQUIPMENTS
• Stainless steel or polyurethane tightened cloths
• Stainless steel or polyurethane modular panels
• Perforated plates



11 LUBRICATION
Grease or oil




12 DECLOGGING DEVICE
• Bil-vib (balls)
• In option



13 PROTECTION FOR ABRASIVE PRODUCT
• By rubberizing
• By shielding



14 CONTROL
• Variable speed unit
• Engine-brake



4 | HIGHLIGHTS


- LONGEVITY
- ROBUSTNESS
- PROFITABILITY

- MODULARITY
- ERGONOMICS

5 | CHARACTERISTICS

- Surface 0.9 up to more than 30 m²
- Acceleration 3 to 4 G
- Amplitude 2 to 10 mm
- Speed 750 to 1,500 rpm
- Slope 12 to 30 degrees
- Number of decks 1 to 4 decks
- Cuts 1 to more than 300 mm
- Machine weight up to 30 tons
- Length 600 to 10,000 mm
- Width between sides 400 to more than 3,000 mm
- Driving power 2 kW to 75 kW
- Circular vibration in the vertical plane

6 | COMPLEMENT ROL® RANGE




ROL HH with HAND-RAIL

HOOD OPTION :

- Fixed and tense PVC tarp
- PVC tarp with automatic or manual opening
- In boiler-steel

ROL HG with VIBRATING COVER & HOPPER



www.chauvin.fr

info@chauvin.fr

Phone : +33 (0)4 76 09 30 63

Fax : +33 (0)4 76 22 30 54

Head Office

20 rue des Grands Champs

ZI La Rollandière

38360 SASSENAGE - FRANCE

PO Box

BP 70015

38044 GRENOBLE CEDEX 9 - FRANCE

We remain at your disposal for any further information.
CHAUVIN is a subsidiary of SINEX INDUSTRIE.